arXiv:1512.01971v1 [physics.optics] 7 Dec 2015

Subluminal velocity of OAM-carrying beam

Nestor D. Bareza Jr.* **and Nathaniel Hermosa**
National Institute of Physics, University of the Philippines Diliman, Quezon City, Diliman 1101
*Corresponding author: nbareza@nip.upd.edu.ph

Abstract

We report a consequence of the orbital angular momentum (OAM) of a beam to its group velocity. We calculate the group velocity v_g of Laguerre-Gauss beam (LG) with ℓ and at $p = 0$. The v_g reduction of LG beam even in free space is observed to have dependence on both orbital or winding number ℓ and the beam's divergence θ_0. We found that light possessing higher ℓ travels relatively slower than that with lower ℓ values. This suggests that light of different OAM separate in the temporal domain along propagation and it is an added effect to the dispersion due to field confinement. Our results are useful for treating information embedded in light with OAM from astronomical sources and/or data transmission in free space.

Keywords: Wave propagation (42.25.Bs), Orbital angular momentum of light

The speed of light c, is constant. This fact has been a pillar of modern physics since the derivation of Maxwell and in Einstein's postulate in Special Relativity, and it has been a basic assumption in light's various applications. A physical beam of light however, has a finite extent such that even in free space it is by nature dispersive. The confinement of the field changes its transverse wave vector, hence, altering the light's group velocity v_g. Confined light therefore, would have its v_g that is not equal to c.

Recently, Giovannini et al showed thru experiments, backed by calculations, that spatially structured light indeed travels slower than c [1]. That is, there is a decrease of group velocity for structured light. Although the phenomenon can be explained classically, they used a Hong-Ou-Mandel interferometer to measure the lag of a structured photon compared to a photon which was not structured. In their experiment, the slowing of light is due to dispersion in free space. They performed their experiment with a Bessel beam and a Gaussian beam. Alfano and Nolan remarked that by considering dispersion relation, Bessel beam can be very slow near a critical frequency which can be used as optical buffer in free space [2]. Slowing light due to its structure is different from slowing light with materials.

A structured light that has recently gained much attention are beams endowed with orbital angular momentum (OAM). It has a phase factor of the form $\ell\varphi$, where φ is the azimuthal angle and ℓ is the number of 2π windings around φ. First investigated by Allen et al, these beams have Poynting vectors that spiral along the direction of propagation [3]. The skewness of the Poynting vector with respect to optical axis z is inversely related to radial distance r [4]. The wavefront for this kind of beam which is helical is illustrated in Figure 1*a*. The negative ℓs will yield the same wavefronts but of opposite helicities. The intensity profile of this kind of beam is a donut shape with smooth radial gradients as shown in Figure 1*b*. Each photon in such beams carries an OAM value of $\ell\hbar$. This beam's property has led to a myriad of applications from optical tweezing and micromanipulation [5,6], to free space information [7], to tranverse Doppler effect [8], and in astrophysics [9]. In the paraxial regime, these beams form a complete basis set such that it can be used as a tool in quantum information processes [10–12].

It is therefore important to ask: *What is the effect of the OAM of a beam on its group velocity?* The consequences are extensive. The most important of which is the different time of arrival of information even in free space propagation. This is similar to modal dispersion in fiber, a serious limitation in optical fiber communication. The promised massive information when using beams with OAM will have an issue. Information embedded in these beams will not arrive at the same time and some corrections are then necessary.

In this letter, we report our calculation on the reduction of v_g's due to the beam's OAM. The analytical expression is exact with just a factor ℓ and our expression reduces to the results of Giovannini when $\ell = 0$.

We follow the derivation in [1], with a Laguerre-Gauss (LG) beam in the lowest radial order $p = 0$ which is given by

$$\psi_{l,p=0}(r,\varphi) \sim r^{|\ell|} exp\left(-\frac{r}{w(z)}\right)^2 exp\left(-i\ell\varphi\right) exp\left(\frac{-ikr^2}{R(z)}\right), \tag{1}$$

where $w(z) = w_o\sqrt{1+\frac{z^2}{z_R^2}}$, $R(z) = \frac{z^2+Z_R^2}{z}$ and $Z_R = \frac{1}{2}kw_o^2$ is the Rayleigh length. This beam spreads along propagation as illustrated in Figure 1*c*. In the far-field, the divergence due to Gaussian term which is represented by opening angle θ_o can be simply expressed in terms of minimum beam waist w_o and wavevector k_o:

$$\frac{\theta_o}{2} = \frac{2}{k_o w_o}. \tag{2}$$



Figure 1: Illustrations of (a) LG wavefront for ℓ=1 with its corresponding (b) intensity profile and (c) LG beam spreading through propagation.

The effective group velocity of a beam propagating along z and with central frequency ω_0 is

$$v_g^{(z)} = \left(\frac{\partial^2\Phi}{\partial z\partial\omega}\right)_{\omega_0}^{-1}, \tag{3}$$

where Φ is the phase profile. Φ can be represented as the complex argument of functional value of ψ, which is the transverse profile in a scalar approximation as in [1]:

$$\Phi = arg\,\langle\psi(z,\omega_o)|\psi(z,\omega)\rangle \tag{4}$$

Fields confined within a volume would have an effective v_g as the harmonic mean of the velocity and weighted by the local intensity. The average v_g for path interval $\Delta z = z_2 - z_1$ is then given by,

$$v_g = \left(\frac{1}{z_2-z_1}\int_{z_1}^{z_2}\left(\frac{\partial^2\Phi}{\partial z\partial\omega}\right)_{\omega_0}dz\right)^{-1} = \Delta z/\left[\frac{\partial}{\partial\omega}\left(arg\,\langle\psi\left(z,\omega_0\right)|\psi\left(z,\omega\right)\rangle\right)_{\omega_0}\right]_{z_1}^{z_2}. \tag{5}$$

The denominator in the rightmost side denotes the time Δt it takes for the structured light to travel Δz with an added path length δz due to its altered wavevector that also contains some transverse components. They are related by $\Delta t = (\Delta z + \delta z)/c$. The added path length can then be expressed in terms of complex argument of the functional value of ψ in wavevector domain with k_o as the central wavevector:

$$\delta z = \left[\frac{\partial}{\partial k}\left(arg\,\langle\psi\left(z,k_0\right)|\psi\left(z,k\right)\rangle\right)_{\omega_0}\right]_{z_1}^{z_2} - \Delta z. \tag{6}$$

Now, v_g can be reformulated in terms of δz given in (6) by the following,

$$v_g = c/\left(1 + \frac{\delta z}{\Delta z}\right). \tag{7}$$

Translating the spatial dependence of this v_g into wavevector, we solve (6) in the paraxial regime whose wave equation is

$$\frac{\partial \psi}{\partial z} = \frac{i}{2k}\nabla_\perp^2 \psi + ik\psi \tag{8}$$

where $\nabla_\perp^2$ operator is the transverse laplacian, which can also be written in terms of quantum mechanical operator to transverse wavevector $\hat{k_\perp} = -i\nabla_\perp$. In this regime, the wavefunction evolves from z_1 to z_2 by $|\psi(z_2,k)\rangle = \exp\left[\Delta z\left(\frac{i}{2k}\nabla_\perp^2 + ik\right)\right]|z_1,k\rangle$. By taking an inner product of $\psi(z_2,k)$ and subsituting result to (6), we obtain the relations:

$$\frac{\delta z}{\Delta z} = \frac{\langle \hat{k}_\perp^2 \rangle_{|\psi(z_1,k_o)\rangle}}{2k_o^2} \tag{9}$$

so that (5) becomes,

$$v_g = \frac{c}{1 + \frac{\langle k_\perp^2 \rangle}{2k_o^2}} \tag{10}$$

where,

$$\langle k_\perp^2 \rangle = \frac{\langle \psi | k_\perp^2 | \psi \rangle}{\langle \psi | \psi \rangle}. \tag{11}$$

Using LG beam with ℓ and at $p = 0$ as the wavefunction, we substitute (1) to (11) in order to have

$$\langle k_\perp^2 \rangle = \frac{2}{w_0^2}(|\ell| + 1). \tag{12}$$

And the group velocity for such beam is given by,

$$v_g = \frac{c}{1 + \left(\frac{1}{k_0 w_0}\right)^2 (|\ell| + 1)} = \frac{c}{1 + \left(\frac{\theta_0}{4}\right)^2 (|\ell| + 1)} \tag{13}$$

where $1/k_0 w_0$ is replaced by the opening angle of the beam $\theta_0/4$ for a more intuitive picture. The absolute value appearing in ℓ indicates that same v_g reduction is obtained regardless of ℓ polarity or wavefront helicity. When $\ell = 0$, $v_g = c/\left(1 + \frac{1}{k_0^2 w_0^2}\right)$ which is consistent with the calculation for Gaussian beam in [1].

Eqn. (13) is the most important result in this letter. This consequently shows that an LG beam is subluminal and dispersive even in free-space. The v_g reduction depends on both orbital order ℓ and far field beam divergence θ_o. For light with OAM, we can think that the added path length due to beam divergence increases by a factor of $|\ell| + 1$. This factor is consistent to the conservation of total linear momentum in the system. Moreover, this factor amplifies the time delay for light to travel the path difference Δz hence, a lower v_g occurs. In the work of Giovannini et al [1], the added path length comes from the radial component of Poynting vector with respect to the optical axis. In equation (12), we show that even a Poynting vector with angular component with respect to the optical axis can also contribute to the path.

The v_g reduction is depicted by displaying plots between the ratio v_g/c versus ℓ for different w_o values, with the beam's central wavelength set to $\lambda_0 = 632.8nm$, as shown in Figure 2(a). All v_g/c values obtained are lower than unity implying the subluminal behavior of LG beams. Notice first that even for $\ell = 0$, the subluminality of v_g is apparent for different w_o values, and that v_g is even more reduced for relatively smaller w_o. This holds true since, for a certain λ_o, relatively lower w_o yields larger far-field beam divergence. As the beam propagates for such case, the field confinement in the transverse structure is amplified. Now as ℓ increases, v_g becomes even slower, which can be observed for different w_o values. This indicates that a beam with higher orbital order will have greater path length δz, which is evident when relating (12) to (9). A simple calculation based on (13) gives an almost 5% speed reduction for a beam with $w_0 = 2\mu m$ and $\ell = 20$.

Furthermore, eqn. (13) shows that light-carrying OAM is experiencing free-space dispersion. The effective group index of refraction n_g is given by,

$$n_g = 1 + \left(\frac{\theta_0}{4}\right)^2 (|\ell| + 1) \tag{14}$$

It can be observed from plots displayed in Figure 2(b) that for any w_o values, n_g is linearly related to $|\ell|$. Thus, beams of different ℓ values that are initially propagated simultaneously will have different time delays after travelling the same Δz. This makes LG beams separate in the temporal domain which consequently demands corrections in its applications such as in data transmission/communication, in multiplexing, and in OAM spectrum detection [13–16].



Figure 2: Plots of (a) v_g/c and (b) n_g versus $|\ell|$ for different minimum beam waist w_o values.

Padgett et al. demonstrate that for a given beam size, the far-field opening angle increases with increasing OAM [17]. This consequently suggests that a larger aperture is required when receiving beams with relatively higher OAM. The ℓ-dependence of v_g for LG beams that we reported may be incorporated to such receiving optical system. A time-controllable receiving aperture size can be programmed according to computed delays prior to the arrival of beams. As opposed to the beam divergence relation presented in (2) which is due to skewness of Poynting vector with respect to optical axis, they also considered the contribution of normal diffractive spreading by the standard deviation of the spatial distribution. They derived the far-field beam divergence α_ℓ to be dependent on $|\ell|$ in the following manner,

$$\alpha_\ell = \sqrt{\frac{|\ell| + 1}{2}} \frac{2}{k_o w_o} \tag{15}$$

Reformulating the calculated v_g for LG beams according to this beam divergence definition, we get a more compact form given by

$$v_g = \frac{c}{1 + \frac{\alpha_\ell^2}{2}} \tag{16}$$

In an actual experiment where a Gaussian laser beam traversed a fork hologram, the intensity profile deviates from the LG expression given by eqn. (1) and is expressed as Kummer function. Kummer beams yielded by confluent hypergeometric function, are expressed as the difference between two Bessel functions [18]. The wavefunction for such case is extensively derived in [19] in which the model is more apparent in the far-field region. This is however beyond the scope of this letter.

In conclusion, we have derived the group velocity v_g of LG beam that depends on both orbital order $|\ell|$ and far-field beam divergence θ_o. This result shows that light is both subluminal and dispersive even in free space. This would have far-reaching consequences on the OAM beam's applications.

References

[1] Giovannini, D., et al. "Spatially structured photons that travel in free space slower than the speed of light." *Science* 347.6224 (2015): 857-860.

[2] Alfano, R., and Nolan, D. "Slowing of Bessel light beam group velocity." *Optics Communications* 361 (2016): 25-27.

[3] Allen, Les, et.al. "Orbital angular momentum of light and the transformation of Laguerre-Gaussian laser modes." *Physical Review A* 45, no. 11 (1992): 8185.

[4] Leach, Jonathan, et al. "Direct measurement of the skew angle of the Poynting vector in a helically phased beam." *Optics express* 14.25 (2006): 11919-11924.

[5] Curtis, Jennifer E., Brian A. Koss, and David G. Grier. "Dynamic holographic optical tweezers." *Optics Communications* 207.1 (2002): 169-175.

[6] Galaja, Peter, et al. "Rotational Optical Micromanipulation with Specific Shapes Built by Photopolymerization." *Twisted Photons: Applications of Light with Orbital Angular Momentum, First Edition* (2011): 117-141.

[7] Gibson, Graham, et al. "Free-space information transfer using light beams carrying orbital angular momentum." *Optics Express* 12.22 (2004): 5448-5456.

[8] Rosales-Guzman, Carmelo, et al. "Experimental detection of transverse particle movement with structured light." *Scientific reports* 3 (2013).

[9] Berkhout, Gregorius CG, and Marco W. Beijersbergen. "Method for probing the orbital angular momentum of optical vortices in electromagnetic waves from astronomical objects." *Physical review letters* 101.10 (2008): 100801.

[10] Mair, Alois, et al. "Entanglement of the orbital angular momentum states of photons." *Nature* 412.6844 (2001): 313-316.

[11] D'Ambrosio, V., et al. "Orbital angular momentum for quantum information processing." *SPIE Photonics Europe. International Society for Optics and Photonics*, 2012.

[12] Molina-Terriza, Gabriel, Juan P. Torres, and Lluis Torner. "Twisted photons." *Nature Physics* 3.5 (2007): 305-310.

[13] Wang, Jian, et al. "Terabit free-space data transmission employing orbital angular momentum multiplexing." *Nature Photonics* 6.7 (2012): 488-496.

[14] Karimi, Ebrahim, et al. "Time-division multiplexing of the orbital angular momentum of light." *Optics letters* 37.2 (2012): 127-129.

[15] Tamburini, Fabrizio, et al. "Encoding many channels on the same frequency through radio vorticity: first experimental test." *New Journal of Physics* 14.3 (2012): 033001.

[16] Lavery, Martin PJ, et al. "Efficient measurement of an optical orbital-angular-momentum spectrum comprising more than 50 states." *New Journal of Physics* 15.1 (2013): 013024.

[17] Padgett, M., et al. "Divergence of an orbital-angular-momentum-carrying beam upon propagation." *New Journal of Physics* 17.2 (2015): 023011.

[18] Ricci, F., W. Lffler, and M. P. van Exter. "Instability of higher-order optical vortices analyzed with a multi-pinhole interferometer." *Optics express* 20.20 (2012): 22961-22975.

[19] Janicijevic, Ljiljana, and Suzana Topuzoski. "Fresnel and Fraunhofer diffraction of a Gaussian laser beam by fork-shaped gratings." *JOSA A* 25.11 (2008): 2659-2669.